

# GRIT TEKNİK ÖZELLİKLER / EN ISO 10582

	ÜRÜN ÖZELLİKLERİ	STANDART	2,50 mm Dry Back	5,00 mm Click/Loose-Lay
	Toplam Kalınlık	EN-ISO 24346	2,50 mm	5 mm
	Aşınma Tabakası Kalınlığı	EN-ISO 24340	0,55 mm	0,55 mm
	Koleksiyon		26	26
	Kullanım Sınıflaması	EN-ISO 10582	Class 23 / Class 33 / Class 42	Class 23 / Class 33 / Class 42
	Karo Ebadı	EN-ISO 24342	Dry Back: 305,0 x 610,0 mm Dry Back: 457,2 x 457,2 mm Dry Back: 610 x 610 mm	Loose Lay: 305,0 x 610,0 mm Loose Lay: 610 x 610 mm Click: 296,2 x 601,2 mm
	Plaka Ebadı	EN-ISO 24342	Dry Back: 177,8 x 1219,2 mm	Loose Lay: 177,8 x 1219,2 mm Click: 169,0 x 1210,4 mm
	Paket içi adet: Karo		Dry Back: 305,0 x 610,0 mm, 3,16 m2 17 pcs. Dry Back: 457,2 x 457,2 mm, 1,67 m2 8 pcs. Dry Back: 610 x 610 mm, 2,97 m2 8 pcs.	Loose Lay: 305,0 x 610,0 mm, 1,48 m2 8 pcs. Loose Lay: 610 x 610 mm, 1,48 m2 4 pcs. Click: 296,2 x 601,2 mm, 1,42 m2 8 pcs.
	Paket içi adet: Plaka		Dry Back: 177,8 x 1219,2 mm, 3,67 m2 17 pcs.	Loose Lay: 177,8 x 1219,2 mm, 3,67 m2 17 pcs. Click: 169,0 x 1210,4 mm, 1,63 m2 8 pcs.



Toplam Ağırlık

EN-ISO 23997

4.480 kg/m<sup>2</sup>

9.480 kg/m<sup>2</sup>



Aşınma Dayanımı

EN 660-2

Group T

Group T



Sandalye Tekerlekleri ile  
Aşınma

No Effect

No Effect



Kalıcı Batma

ISO 24343-1

0,10 mm

0,10 mm



Renk Değişimi

EN ISO 105-B02

6

6



Kimyasallara Karşı Direnç

EN ISO 26987

Very Good

Very Good



Boyutsal Kararlılık

EN-ISO 23999

0,25%

0,15%



Termal İletkenlik

ISO 8302:1991

0,0134 m<sup>2</sup> K/W

0,0193 m<sup>2</sup> K/W



Alev Yayılması

EN 13501-1

BFL-S1

BFL-S1



Kayma Direnci

EN 13893

DS

DS



Akustik Ses Yalıtımı

EN ISO 10140-1-  
5:2010 EN ISO 717-  
2:2013

6 dB

8 dB



Formaldehit

EN 717-1:2014

E1

E1



Statik Elektriksel Yükleme

EN 1815

-

2 kV

## ÜRÜN ÖZELLİKLERİ

## STANDART

**2,50 mm  
Dry Back**

**5,00 mm  
Click/Loose-Lay**



Toplam Kalınlık

EN-ISO 24346

2,50 mm

5,00 mm



Aşınma Tabakası Kalınlığı

EN-ISO 24340

0,70 mm

0,70 mm



Koleksiyon

26

26



Kullanım Sınıflaması

EN-ISO 10582

Class 23 / Class 34 / Class  
43

Class 23 / Class 34 / Class 43

## ÜRÜN ÖZELLİKLERİ

## STANDART

2,50 mm  
Dry Back

5,00 mm  
Click/Loose-Lay



Karo Ebadı

EN-ISO 24342

Dry Back: 305,0 x 610,0 mm  
Dry Back: 457,2 x 457,2 mm  
Dry Back: 610 x 610 mm

Loose Lay: 305,0 x 610,0 mm  
Loose Lay: 610 x 610 mm  
Click: 296,2 x 601,2 mm



Plaka Ebadı

EN-ISO 24342

Dry Back: 177,8 x 1219,2  
mm

Loose Lay: 177,8 x 1219,2 mm  
Click: 169,0 x 1210,4 mm



Akustik Ses Yalıtımı

EN ISO 10140-1-5:2010 EN ISO 717-2:2013

6 dB

8 dB



Formaldehit

EN 717-1:2014

E1

E1



TS EN 14041



EN ISO 10582



Phthalate Free



23



33



34



42



43

